

therm-x2® Piano/Line K/V/VM
Resa termica a norma in Watt

Temperatura ambiente 20°C
Temperatura dell'acqua 75/65°C
di riscaldamento

Altezza mm		205*		305					405					505				
Tipo		22	33	10	11	12	22	33	10	11	12	22	33	10	11	12	22	33
Larghezza mm																		
405	W 75/65°C			117	197	266	365	509	149	251	326	456	648	181	303	386	542	777
505	W 75/65°C			145	246	332	456	634	186	313	407	568	808	226	378	482	676	969
605	W 75/65°C	395	587	174	295	397	546	760	223	374	487	681	967	270	453	577	810	1160
705	W 75/65°C	460	685	203	343	463	636	886	260	436	568	793	1127	315	528	673	944	1352
805	W 75/65°C	526	782	232	392	529	726	1011	297	498	648	906	1287	360	603	768	1078	1544
905	W 75/65°C	591	879	261	441	595	816	1137	334	560	729	1018	1447	405	678	863	1212	1736
1005	W 75/65°C	656	976	289	489	660	907	1262	371	622	809	1131	1607	449	753	959	1346	1928
1105	W 75/65°C	722	1073	318	538	726	997	1388	408	684	890	1243	1767	494	828	1054	1480	2120
1205	W 75/65°C	787	1170	347	587	792	1087	1514	445	746	970	1356	1927	539	903	1150	1613	2311
1305	W 75/65°C	852	1267	376	636	857	1177	1639	482	808	1051	1468	2087	583	977	1245	1747	2503
1405	W 75/65°C	918	1364	405	684	923	1267	1765	518	870	1131	1581	2247	628	1052	1340	1881	2695
1605	W 75/65°C	1048	1559	462	782	1054	1448	2016	592	993	1292	1806	2567	717	1202	1531	2149	3079
1805	W 75/65°C	1179	1753	520	879	1186	1628	2267	666	1117	1453	2031	2886	807	1352	1722	2417	3462
2005	W 75/65°C	1309	1947	577	976	1317	1809	2518	740	1241	1614	2256	3206	896	1502	1913	2685	3846
2305	W 75/65°C	1505	2238	664	1123	1514	2079	2895	851	1427	1856	2593	3686	1030	1726	2199	3086	4421
2605	W 75/65°C	1701	2530	750	1269	1711	2350	3272	961	1612	2097	2931	4166	1164	1951	2485	3488	4997
3005	W 75/65°C	1962	2918	865	1463	1974	2711	3775	1109	1860	2419	3381	4805	1343	2251	2867	4024	5764

* senza funzionamento x2

Altezza mm		605					905				
Tipo		10	11	12	22	33	10	11	12	22	33
Larghezza mm											
405	W 75/65°C	212	356	448	627	897	303	512	648	876	1211
505	W 75/65°C	265	443	559	782	1119	377	639	807	1093	1510
605	W 75/65°C	317	531	669	937	1340	452	765	967	1309	1808
705	W 75/65°C	369	619	780	1092	1562	527	892	1127	1526	2107
805	W 75/65°C	422	707	890	1247	1783	601	1018	1287	1742	2406
905	W 75/65°C	474	795	1001	1402	2005	676	1145	1447	1958	2705
1005	W 75/65°C	527	882	1112	1557	2226	751	1271	1607	2175	3004
1105	W 75/65°C	579	970	1222	1712	2448	825	1398	1767	2391	3303
1205	W 75/65°C	631	1058	1333	1867	2669	900	1524	1927	2608	3602
1305	W 75/65°C	684	1146	1443	2021	2891	975	1651	2087	2824	3901
1405	W 75/65°C	736	1234	1554	2176	3112	1050	1777	2247	3040	4200
1605	W 75/65°C	841	1409	1775	2486	3555	1199	2030	2566	3473	4798
1805	W 75/65°C	946	1585	1996	2796	3998	1348	2283	2886	3906	5396
2005	W 75/65°C	1051	1760	2218	3106	4441	1498	2536	3206	4339	5993
2305	W 75/65°C	1208	2024	2549	3570	5106	1722	2916	3686	4988	6890
2605	W 75/65°C	1365	2287	2881	4035	5771	1946	3295	4165	5637	7787
3005	W 75/65°C	1575	2638	3324	4655	6657	2245	3801	4805	6503	8983

therm-x2[®] Piano/Line K radiatore sostitutivo
 Resa termica a norma in Watt

Temperatura ambiente 20°C
 Temperatura dell'acqua di riscaldamento 75/65°C

Altezza mm		559			959		
	Tipo	12	22	33	12	22	33
Larghezza mm	Watt/m 75/65°C	1035	1453	2081	1682	2213	3148
405	W 75/65°C	419	589	843	681	896	1275
505	W 75/65°C	523	734	1051	849	1118	1590
605	W 75/65°C	626	879	1259	1018	1339	1905
705	W 75/65°C	730	1024	1467	1186	1560	2220
805	W 75/65°C	833	1170	1675	1354	1782	2534
905	W 75/65°C	937	1315	1883	1522	2003	2849
1005	W 75/65°C	1040	1460	2092	1691	2224	3164
1105	W 75/65°C	1144	1606	2300	1859	2446	3479
1205	W 75/65°C	1247	1751	2508	2027	2667	3794
1305	W 75/65°C	1351	1896	2716	2195	2888	4108
1405	W 75/65°C	1454	2042	2924	2363	3110	4423
1605	W 75/65°C	1661	2332	3340	2700	3552	5053
1805	W 75/65°C	1868	2623	3756	3036	3995	5683
2005	W 75/65°C	2075	2913	4173	3373	4437	6312
2305	W 75/65°C	2386	3349	4797	3877	5101	7257
2605	W 75/65°C	2696	3785	5421	4382	5765	8201
3005	W 75/65°C	3110	4367	6254	5055	6651	9460

Interasse 350 mm (altezza 405 mm) vedere tabella radiatori compatti Piano/Line